

**FAST** HF CHARGER



# REVOLUTION

## FAST BATTERY CHARGERS

### Modular High Frequency Smart Chargers

The **REVOLUTION** Series is an innovative line of ultra-high frequency battery chargers that incorporates cutting-edge modular power design that delivers peak efficiency greater than 93% and efficiencies greater than 90% throughout the entire charge cycle. As the charge cycle progresses and the output current tapers down, the charger will turn off unneeded modules, allowing the remaining modules to operate at peak efficiency.

The **REVOLUTION** Series is a combination of cutting-edge charging and energy management technologies, with a smaller footprint, lower acquisition costs, easy maintenance, and flexible configurations, which makes updating your fleet of electric lift trucks a more attractive investment than ever before. Free your operation from spare batteries, daily battery changes, battery storage areas, and energy inefficient charging!

#### Unmatched energy savings

- › Highest charging efficiency throughout the entire charge cycle
- › Lowest energy costs related to battery charging
- › Latest generation MOSFET power conversion technology
- › CEC Compliant+
- › Minimize or even avoid peak demand cost related to battery charging

#### Innovative modular architecture

- › Multi-voltage 1.3kW power modules, that can be combined to produce over 30 kW output
- › Wireless Communication
- › "Plug and Play" utility makes expansion easy
- › No Downtime! Charger remains operational if a power module fails



**Total Charge Cycle Efficiency**  
> 90%

**Peak Efficiency**  
> 93%



#### Cost effective with long term savings

- › Low initial cost versus traditional fast chargers
- › Charger can be programmed for all battery types (lithium, flooded, low maintenance, gel, and sealed)
- › 24V through 80V battery capabilities, with maximum current remaining constant based on module voltage rating
- › With these unique design features, the **REVOLUTION** eliminates the need to replace chargers as your lift truck battery fleet changes in the future

### Variable Configuration Architecture


The **REVOLUTION** series of chargers are modular concept chargers offering multiple configuration capability. The independent power modules, installed in parallel, allow the user to add individual modules, increasing the charger's output for a minimal upgrade cost.

The parallel module design provides built-in redundancy that ensures that in the event of a module failure, the charger will continue to operate at a slightly lower current output, until the problematic module is replaced. In the event of a module failure, the module can quickly be replaced. The charger display will indicate the module failure and with the removal of a few screws, the faulted module can simply be unplugged and a new module plugged in, replace the door, re-energize the charger, and it is back to work. The unique modular architecture provides unmatched value, as diagnosis and repair of a **REVOLUTION** is the simplest and fastest of any charger in service today.

The **REVOLUTION** charger, when combined with the Viking Intel data logger, has the ability to be multi-voltage\*, allowing the charger to automatically charge a wide range of batteries and amp hour capacities, making the **REVOLUTION** the last charger you will need to purchase.

### REVOLUTION Series Features

- › Modular architecture that is scalable and reliable
- › Small footprint and light weight with wall, post, or rack mounting options
- › Viking Intel battery data logger option allows the **REVOLUTION** charger to have multi-voltage\*capabilities, giving the charger the ability to automatically adapt to the battery voltage and AH capacity
- › PowerCharge.NET monitoring system option allows you to collect and analyze fleet utilization information from a single location, optimizing your cost savings
- › The most efficient charger throughout the entire charge cycle



## REVOLUTION Fast Charger Specifications

Model	Module Size	Output Voltage	4kW	5kW	6kW	8kW	9kW	10kW	12kW	13kW	14kW	15kW	18kW	21kW	23kW	26kW	29kW	31kW
Maximum Current Output	5X	36	36V	90	120	150												
		48	36V/48V	75/67	100/90	125/112												
	8X	36	36V			150	180	210	240									
		48	36V/48V			125/112	150/135	175/157	200/180									
	12X	36	36V					240	270	300	330	350						
		48	36V/48V					200/180	225/202	250/225	275/247	300/270						
	16X	36	36V									360	420	480				
		48	36V/48V									300/270	350/315	400/360				
	24X	36	36V												540	600	660	700
		48	36V/48V												450/405	500/450	550/495	600/540
Number of Modules			3	4	5	6	7	8	9	10	11	12	14	16	18	20	22	24
Charger kW Rating			3.9	5.2	6.5	7.8	9.1	10.4	11.7	13.0	14.3	15.6	18.2	20.8	23.4	26.0	28.6	31.2
Input Current Draw			5.5	7.4	9.2	11.1	12.9	14.8	16.6	18.5	20.3	22.2	25.9	29.6	33.3	37.0	40.7	44.4
AC Breaker			5X: 15A		8X: 20A		12X: 30A		16X: 40A		24X: 60A							
Max. Input Current			5X: 10A		8X: 15A		12X: 22A		16X: 30A		24X: 44A							
Input Voltage			480VAC, 3-phase ± 10%															
Efficiency			Total charge cycle efficiency > 90%															
			Peak charging efficiency > 93%															
User Interface			LCD/Keypad, Ethernet (optional)															
Cooling			Forced air (fans)															
Dimensions (WxDxH)			5X: 12.5" x 8.5" x 20.25"				8X: 18.5" x 9.5" x 21"				12X: 26.5" x 9.5" x 21"							
			16X: 22" x 10" x 48"				24X: 30" x 10" x 48"											
Weight			5X: ≤ 56 lbs		8X: ≤ 81 lbs		12X: ≤ 120 lbs		16X: ≤ 210 lbs		24X: ≤ 300 lbs							
Certifications			UL and cUL listed; CEC Compliant*															

Based on 40% start rate